



**CBTC Decoded.
Advancing Rail Safety
Through Transparency
and Technology**

Presented by: Alexander Impastato

Date: 08/07/25

Disclaimer



The information presented is my own and not those of my employer or its clients.



All material sourced from publicly available documents. (Sources will be listed at end of presentation).



No proprietary information included.



For CBTC educational purposes only.

Agenda



Part I Intro and CBTC Proposal



Part II Fundamentals and History



Part III Architecture & Operation



Part IV Development and Integration



Part V Design Considerations + Future Trends.



Part VI Q&A

Part 1

Introduction and Proposal


- Fixed block signaling issues.
- Why a new signaling approach is needed.

19th century: track circuits and colored wayside signals..

- 19th century: track circuits and colored wayside signals. Stop/Proceed.
- Key Innovation: **Track-circuit & fixed signals**
Electric track circuits detect train presence
- Key Innovation: Colored wayside signals tell drivers “stop / proceed.”
- Why this Mattered: First step toward automated safety that prevented two trains from occupying the same block.



Fixed Block Signaling Constraints




Fixed blocks enforce rigid spacing.

Conservative safety margins slow trains.

Limited real-time data sent to the train dispatcher.


Hardware (relays, track circuits) aging & failure-prone.



Three aspect Signaling System


- Green = 2+ blocks clear ($\geq 2 \times \text{SBD}$)
- Yellow = 1 block clear ($\geq 1 \times \text{SBD}$)
- Red = train ahead in next block
- Each signal is placed 1 safe braking distance (SBD) apart.
- Track circuits detect presence in fixed blocks.
- System knows train is “somewhere” in block — not exact location.
- This is the basis of fixed-block signaling.

Fixed Block Limitation Visualization





Fixed Block Limitation Visualization




Red blocks = occupied blocks.

Yellow Blocks = buffer zones.
Trains cannot enter these zones
neither.

Unused track between blocks
wastes capacity.

More trains can't enter until block
clears.



Fixed Block Signaling drawbacks.



Peak demand exceeds
~25–27 trains/hour limit.
Ex. NYCT 7 Line.




Station crowding and
longer wait times.
Dangerous and unsanitary
environment.



Building new tunnels for
more trains costs billions
& takes decades. We
don't have the space
neither.

Fixed Block Signaling Drawbacks.

- The fixed block signaling system's requirement for a specific gap between trains constrained the track's maximum speed limit.
- Fixed block signaling system also relied on human operators, who could make mistakes and cause delays when deciding how to move trains.





CBTC (Moving block Signaling) Propoaal



GOAL: INCREASE
CAPACITY ON EXISTING
INFRASTRUCTURE.



ENHANCE SAFETY &
RELIABILITY.



PROVIDE PRECISE TRAIN
LOCATION DATA TO
TRAIN DISPATCHER



ENABLE HIGHER
AUTOMATION LEVELS.

Part 2


Fundamentals
and History

Historical Advancements in
Transit's signaling system
leading to CBTC.

What Is CBTC?



CONTINUOUS AUTOMATIC
TRAIN CONTROL VIA RADIO.



USES MOVING-BLOCK
SEPARATION.



ENABLES ATP, ATO, ATS
SUBSYSTEMS.

CBTC Benefits Overview

+20 – 50%
capacity increase.

Automatic
protection
eliminates
collisions.

Higher service
reliability; fewer
signal failures.

Foundation for
driverless
operation.

Evolution of Railway Signaling

- 19th century: track circuits and colored wayside signals. (Covered)
- Mid-20th: relay-based ATP (Automatic Train Protection) Relay based speed enforcement. Cab Signaling
- 1980s: first moving-block radio systems. Ex. SELTRAC on Scarborough RT Toronto Canada
- 1990s-2000s: digital CBTC lines open. Paris Line, L Canarsie Line, High Speed rail, PTC.


Mid-20th:
relay-based
ATP
(Automatic
Train
Protection)
Cab
Signaling

- Cab signaling displays signal aspects in-cab via coded track circuits. (Speed codes)
- Added overspeed protection and richer information than simple red/green signals from wayside, boosting safety.
- Reduced human error and coded in-cab signals gave continuous movement authority.

Cab Signaling. How it works.


- Track circuit sends coded energy through the rails
- Pickup coils on train detect and convert the signal
- Cab equipment displays signal aspect in real time
- Driver must acknowledge restrictive aspects
- If not acknowledged: automatic braking in 8 seconds

Figure 2: Profile-Based Cab Signal System



Automatic Train Protection with Cab Signaling.

- Automatic train protection (ATP) with distance-to-go profile system.
- Train's permitted speed gradually decreases as it approaches the end of its movement authority, ensuring a controlled and safe stop.



Cab signaling further advancements

- Speed enforcement via onboard Brake Assurance (BA)
- BA device verified actual braking using motion of mercury tube
- Reduced need for wayside signals (ABS)
- Digital track circuits enabled Distance-to-Go (DtG) cab signaling
- Binary FSK modulation used to transmit speed + target info
- Train calculates its own braking profile using onboard data


1980s: Moving Block Radio Systems.

- 1980s: first moving-block radio systems. Ex. SELTRAC The **Vancouver SkyTrain** (1985). First moving-block CBTC system deployed
- SELTRAC installed on Toronto Scarborough RT (1985)
- Used radio communication and odometry instead of track circuits
- Enabled dynamic train separation and real-time movement authority
- Foundation for modern CBTC systems

1985: SELTRAC


- SELTRAC introduced dynamic, moving-block signaling
- Train separation calculated in real time — no fixed blocks
- Continuous bi-directional communication via inductive loop
- Onboard ATP enforced braking curve from control center
- First deployed on Toronto Scarborough RT and Vancouver SkyTrain (mid-1980s)

SELTRAC Signaling System



SELTRAC Moving Block Architecture.

- SELTRAC architecture: vehicle-based control + inductive loop communication
- VOBC calculates location from odometry, transponders, and radio link
- Zone Controller (VCC) sends movement authority via loops
- No fixed blocks—continuous moving-block enforcement
- Installed on Scarborough RT and Vancouver SkyTrain in mid-1980s



1990s-2000s: Paris Line 1998

- First full CBTC deployment: Paris Line 14 (1998), GoA4
- Onboard ATP: enforces speed limits and safe braking
- ATO: controls acceleration, cruising, and precise station stops
- ATS: manages schedule, dwell times, and passenger info
- Full radio-based, high-resolution train localization
- Eliminated trackside signals and enabled driverless operation



1990s-2000s: CBTC in NYCT

- First CBTC deployment in North America: NYC Subway L Line (2009)
- Siemens Trainguard MT system implemented
- Enabled 20% increase in train throughput
- Reduced signal-related delays and improved on-time performance
- ATO GoA2: Operator remains onboard for door and safety monitoring






1990s-2000s: CBTC in High-Speed rail and PTC

- 2003: Shanghai Maglev launches with CBTC to support 430 km/h operation
- 2018: Research proposes CBTC + PTC hybrid integration for U.S. rail
- CBTC enables real-time control and speed commands
- PTC ensures train stops if limits or signals are violated
- Combined systems enhance safety and operational efficiency

Part 3 CBTC
System
Architecture
and
Operation



Deep dive
into
subsystems
and moving
block logic.

Grades of Automation (GoA) Overview

GoA 1 Manual driving with ATP safeguard

GoA 2 Semi-automatic – ATO drives, driver monitors

GoA 3 Driverless – attendant on board

GoA 4 Unattended – fully automated

IEEE 1474 Standard – Foundation for CBTC Automation

Establishes CBTC
performance and
functional standards
(GoA 1-4).

Core principles:
precise location,
continuous
communication, vital
safety logic.

GoA 1 – Manual + ATP

Driver controls traction & braking.

ATP enforces speed & authority.

Common in legacy systems and during CBTC transition.

GoA 2 – Semi-Automatic

ATO handles speed
profile & stops.

Driver supervises
doors & emergencies.

Widely used on early
CBTC upgrades.

GoA 3 – Driverless Operation

No driver; attendant may ride for passenger service.

System handles all driving functions.

Example: Vancouver SkyTrain (normal ops).

GoA 4 – Unattended Train Operation

Fully automated with
platform screen doors.

Central control oversees
multiple trains. Enable
headways under 90 seconds.

Example: Paris Line 14,
Copenhagen Metro.

CBTC System Architecture Key Components



Train-borne subsystem: VOBC, odometry, ATP/ATO logic



Wayside Zone Controller (ZC): assigns movement authority



Operations Control Center (ATS): manages schedules and supervision



Data Communication System (DCS): radio link + fiber backbone

CBTC System Architecture Block Diagram




Fig. 1. CBTC systems.



Train-Borne Subsystem

- Vehicle Onboard Controller (VOBC) – dual redundant
- Odometry Sensors – tachometer, IMU, Doppler radar
- Radio Transceiver – wireless link to wayside DCS
 - Human-Machine Interface (HMI) – for operator supervision
 - Safety-critical ATP/ATO logic onboard




Localization Accuracy and Spacing Margins


- Odometry drift corrected by transponders (beacons)
- Beacons placed ~300–400 m apart for ground truth reset
- Error between beacons may accumulate up to ± 2 m
- Safety margin (SBD) includes worst-case error + brake distance
- Final spacing = SBD + localization margin + system tolerance

Localization Accuracy and Spacing Margins

- Spacing = SBD + localization error + system delay
- Example:
- Safe Braking Distance (SBD) = 110 m
- Worst-case odometry drift = ± 2 m
- Delay margin = 1.5 m
- Required spacing = $110 + 2 + 1.5 =$
**113.5



Wayside Zone Controller (ZC)



- Computes safe Movement Authority (MA) for every train, 1–10 Hz
- Interfaces with Computer Interlocking (CI) to verify switch & route status
- Exchanges status with ATS/OCC for headway and dwell-time control
- Dual-computer, hot-standby design (SIL-4) for fail-safe redundancy


Computer Interlocking (CI) – Safety Gatekeeper



- Verifies switch & signal alignment before MA issued



- Locks conflicting routes, releases once train clears



- Independent SIL-4 logic (vital programmable controller)



- ZC requests → CI checks & grants “route proven” status


Thales Route control

- Redundant CPU cards (Upper shelves). Dual hot-standby logic; one falls -> ~~the other takes over.~~
- Vital I/O modules (middle). Field contacts for point machines, signals, track circuits
- Relay / interface blocks (lower) Fail-safe output: de-energize-to-safe for points & signals
- Trackside cabinet + signal mast: Shows the CI located near the turnout it protects.



Data Communication System (DCS)

- Dual-band CBTC Wi-Fi (5 GHz + 2.4 GHz fallback) or LTE/5 G option
- Overlapping trackside APs – seamless hand-off < 50 ms (vital traffic)
- Redundant fiber ring backbone – self-heals in < 50 ms
- QoS: vital packets < 100 ms round-trip; non-vital best-effort
- MIMO / cooperative relaying boosts tunnel reliability



Operational Control Center (ATS)

- Real-time train map with predicted arrivals
- Regulates headways by sending speed/dwell commands
- Manages incident response & degraded-mode scenarios
- Interfaces to passenger information & CCTV systems
- Generates performance reports for service planning



ATS: Schedule Regulation Tools


Live headway tracker flags gaps
> ± 10 s

ATO speed offset (± 3 km/h)
smooths the gap

Dynamic dwell extension /
hold at next station

“Skip-and-fill” option during
heavy disruption

Results: 20 % reduction in
bunching delays (NYC L-line
data)



ATS: Incident Management in a CBTC world


- Detects track-circuit failure → flags affected block in <5 s
- Automatically re-routes trains via crossover 17 / track 2
- Issues stop-and-proceed order to nearest train (safe speed 15 km/h)
- Short-turns trailing trains to prevent bunching at terminals
- Pushes realtime alerts to PIDS, staff tablets & maintenance crew

Automatic Train Protection (ATP) How the algorithm works.

-
- Computes safe-braking curve: $v^2 = v_0^2 - 2 a (x - x_0)$
 - Adds safety margin: $MA = SBD + \text{loc error} + \text{delay buffer}$
 - Monitors distance-to-go each 100 ms ($\leq \pm 0.3$ m resolution)
 - Cuts traction & applies service brake when curve touched
 - Triggers emergency brake if MA is exceeded (fail-safe)

ATP: Movement Authority Logic

- MA = position of leading train – safe-braking envelope
- ATP updates curve 5–10 Hz; envelope “slides” with leader
- Following train sees shrinking distance-to-go in real time
- Loss of comms $\Rightarrow$ MA frozen to restrictive value (fail-safe)



ATP: Overspeed Protection “Adaptive cruise control” for Trains.



- Continuously compares actual speed to permitted curve
- 3-step response: audio-visual alert → service brake → emergency brake
- Curve adapts to gradient, mass, adhesion & MA length
- Conceptually like car ACC: maintains safe gap & enforces max speed


Automatic Train Operation (ATO) Precision Driving Benefits

- Executes target speed profile with ± 0.1 m/s accuracy
- Uses coast phases & regen braking $\rightarrow$ 5-10 % energy savings
- Consistent station stops within ± 30 cm of mark
- Reduces dwell-time variance $\rightarrow$ smoother headways
- Minimizes wear on brakes & wheels



ATO: Comfort and Efficiency


- Smooth accel ≤ 1.3 m/s², decel ≤ 1.0 m/s²
- Cruise-coast-brake profile saves 5-10 % energy
- Precision stop within ± 30 cm enables PSDs
- Consistent ride $\rightarrow$ lower motion-sickness reports




ATO: Dynamic Dwell & Door Coordination

-
- Auto-aligns car doors with PSDs (± 30 cm)
 - Real-time passenger count adjusts dwell ± 5 s
 - ATS can hold or release doors to smooth headways
 - Door status + crowd level reported instantly to OCC

Existing fixed block signalling system



Moving block signalling system



Moving Block
vs Fixed
Block. Why
CBTC Packs
more trains.

- Fixed block = track divided into rigid 300-800 m sections
- Only one train per block → long empty gaps at low speed
- Moving block = “safety envelope” slides with each train
- Separation limited only by safe-braking curve, not block length
- Up to 30 % capacity gain on the same infrastructure

Moving vs Fixed Block Visualization

Figure 1: Diagram of a Conventional Fixed Block Signal System






Figure 3: Diagram of a Moving Block (CBTC) Signal System






Safe Braking Distance Calculation


- Core physics: $d = v^2 / (2 a_{\text{serv}}) + \text{margin}$
- Margin = odometry drift + comms delay + 5 % adhesion loss
- Gradient modifier: add / subtract $g \sin \theta$ term
- “Overlap” (5–10 m) appended for worst-case brake failure

Capacity Impact Example

- Legacy fixed-block (600 m) → 25 trains / h
- CBTC moving-block (120 m SBD) → 40 trains / h
- +60 % throughput on same two-track corridor




Part 4. Deployment and Intergration





Greenfield VS Brownfield CBTC Projects



Greenfield – Built from scratch; CBTC embedded day-1



► Typical timeline: 4-6 y design-build-commission



► Lower integration risk, single vendor stack



► Cap-ex $\approx$ US \$30-40 M/km (incl. civil works)



Brownfield – Retrofit on an operating line



► Phased migration & dual signalling until cut-over



► Timeline 7-10 y (night/weekend outages)



► Higher O-pex during parallel run; cap-ex $\approx$ US \$12-20 M/km

CBTC Overlay Strategy. Upgrade Without Shutting the Line

-
- New CBTC equipment installed while legacy signals stay live
 - “Shadow running” 3-6 months – CBTC monitors but does not control
 - Segment-by-segment weekend / overnight cut-over windows
 - Legacy kept as fail-safe fallback until full line commissioned

Mixed Operations Challenges

- Legacy train = fixed-block mode;
CBTC train = moving block
- Must apply least-common-denominator headway → capacity penalty
- Dual wayside beacons & overlay logic ⇒ ↑ maintenance & fault points
- Interlocking safety case doubles in complexity
- Agencies aim to limit mixed period to <12 months



“Big-Bang” Cut-Over – Paris Line 1 Case Study

- Entire fleet (MP 05) fitted; legacy drivers re-trained
- CBTC shadow-run 9 months with zero passenger impact
- Overnight switch-over 26 Jan 2013; legacy reached safe-state, CBTC became vital
- Achieved GoA 4 next morning – no fallback required



Testing & Commissioning- Staged Validation Path

- Factory Acceptance Test (FAT) – hardware & software bench-tested
- Site Acceptance Test (SAT) – power-up & static I/O checks on track
- Dynamic nighttime runs – no passengers, verify braking curves
- Shadow operation – CBTC calculates MA while legacy controls train
- Trial service – passengers aboard with safety staff riding, 30-90 days
- Safety Case approval by regulator
→ revenue GoA level granted



Training & Change Management. The “Soft” Success Factors.

- Up-skill drivers → attendants:
simulator + GoA 2 in-cab drills
- 10-week maintainer programme:
VOBC swap, ZC diagnostics, DCS RF
survey
- Public-facing campaign: “Trains
now run automatically—stand clear
of doors”
- Emergency procedures rewritten
for unattended operation (GoA 4)



NYC Subway CBTC Program. – Scale of the Retrofit

- World's oldest large metro (opened 1904); 1,000 km of track
- Completed: L (2009) & 7 (2018) – 40 tph and 32 tph peaks
- In progress: Queens Blvd, 8th Avenue Fulton Avenue, Astoria corridors
- \$7 B in 2020-2024 & 2025-2029 capital plans; target full network by 2045
- Requires weekend outages + overlay; ~15 km commissioned per year




Canarsie Line (L) – Project Timeline & Milestones

- 1999 – Contract lent to Siemens for Trainguard MT CBTC
- 2000-2004 – Wayside install nights/weekends; VOBC retrofit on 212 cars
- Sept 2005 – First shadow-run segment (Rockaway Av–Broadway Jct)
- Sept 2006 – Full-line shadow complete, legacy coded-cab still vital
- 20 Sept 2009 – Weekend cut-over; revenue GoA 2 service begins Monday
- 2012 – Headway cut to 2 min 15 s (40 tph); on-time performance +12 %



Canarsie Line – CBTC Performance Gains

- Peak throughput +15 % (18 → 20 tph)
- On-time performance 75 % → 90 % (+15 pp)
- Signal-related delays cut 80 % (250 → 50 incidents / yr)



Flushing Line (7) – Lessons Learned from a tougher Retrofit.


Different vendor (Thales) + dual-routed interlockings

Integration & software-sign-off slipped 18 months (2016→2018)

Added “countdown clocks” and real-time dwell-optimizer after go-live

Reliability now rivals Canarsie: OTP 89 % vs 90 % on L

NYC CBTC – Interoperability Plan



Two supplier stacks today
(Siemens + Thales) run on
isolated corridors



2025 spec: “Train-Borne
Controller Common
Interface” for new fleets




RF band & message-format
convergence planned for
QBL / Culver overlap



Goal 2035: any CBTC-
equipped consist can roam
system-wide


Paris Metro. 25 years of GoA 4



Paris Metro Line 14 – Greenfield Success

- Built GoA 4 from day 1; platform-screen doors integral
- Designed for 85–90 s headways $\Rightarrow$ 42 tph theoretical
- MP14 eight-car sets add +30 % capacity vs MP05
- Success triggered north & south extensions (2020–2024)





Paris Line 1 – Brownfield Conversion

- 2010-2012: retrofit of 106-year-old line while carrying 725 k riders/day
- Entire MP05 fleet dual-fitted for CBTC + legacy SACEM during shadow run
- 01:00–05:00 weekend windows replaced 1500 balises & 5 interlockings
- Post-GoA 4: peak capacity 30 → 45 tph (+50 %), dwell-time variance –40 %



Paris Line 4 & Future Projects

- Line 4 brownfield GoA 4 hand-over July 2022 (week-night cut-overs)
- Lines 6 & 11 mid-conversion; service maintained via dual-equipped MP89/MP14
- New Grand Paris Express Lines 15–18: all CBTC from day one
- RATP vision 2030: > 60 % of train-km in unattended operation


Beijing Metro Fast-Track CBTC Deployment

- First GoA 2 line (Airport Express) entered service 2008
- 2023 status: 17 of 27 lines now CBTC-equipped (Siemens, Thales, Bombardier)
- Network carries > 10 million trips / day; 840 km route length
- Typical brownfield corridor finished in < 36 months thanks to nightly block-hours



Beijing Line 10 – World's longest CBTC Loop

- 57 km ring with 45 stations; Siemens Trainguard MT (GoA 2)
- Peak headway 90 s; normal service 2 min even across junctions
- 2014 LTE roll-out caused 2.4 GHz radio drop-outs → migrated to 5.8 GHz & added directional antennas
- After spectrum fix: Radio failure rate ↓ 87 %, punctuality back above 96 %



China's CBTC Strategy

- Since 2015, every new Tier-1 metro line is specified at least GoA 2; most greenfields GoA 4
- “Multiple-vendor, local-license” policy keeps Siemens, Thales, Bombardier and CASCO competing
- Tech-transfer clauses require $\geq 70\%$ onboard & wayside hardware to be manufactured in-country
- Older fixed-block lines upgraded corridor-by-corridor to maintain 10-year capex cycles

Global CBTC Adoption Snapshot (2024)

- 85+ fully-automated (GoA ≥ 3) metro lines now in service worldwide
- > 1 500 route-km of CBTC commissioned since 2010; a further 900 km under construction
- CBTC is the ****de-facto base-spec**** for every green-field heavy-metro project approved after 2020
- Largest brown-field upgrades: New York (425 cars retro-fitted), Paris (Line 1 & 4), Beijing Line 1





Part 5 Design Considerations + Future Trends

Fail-Safe Design Philosophy

Failure mode	Likely cause	Detection / diagnostic	Automatic safe reaction	Dangerous failure rate (λ^d)
CPU-A clock stops	Component ageing, thermal stress	Hardware watchdog not stroked within 100 ms	Brake-apply relay de-energised, VOBC drops to “restricted”	$1.2 \times 10^{-10} \text{ h}^{-1}$
Channel A $\leftrightarrow$ B telegram CRC mismatch	Transient EMI on back-plane bus	16-bit CRC comparison every 50 ms	Both CPUs invalidate movement-authority; train coasts to stop	$3.4 \times 10^{-10} \text{ h}^{-1}$
Brake-release relay welded closed	Contact welding after high inrush	Dual-relay 1-out-of-2 vote disagrees	Second relay opens; pneumatic brakes remain applied	$8.0 \times 10^{-11} \text{ h}^{-1}$

CBTC

Cybersecurity Standards


- IEC 62443 “zones & conduits” model segments wayside, radio and VOBC networks
- CENELEC TS 50701 adapts 62443 for rail-specific threats and ties security levels (SL) to SIL targets
- Layered defence-in-depth: trackside firewalls → DMZ → whitelisted VOBC endpoints
- Continuous risk assessment; patches validated like safety-critical software changes



Communication Network Redundancy

- Dual fiber rings (< 50 ms self-healing) keep the OCC↔wayside backbone alive after any single break.
- Trackside Wi-Fi/LTE radios in A/B pairs give every train two simultaneous RF paths.
- Automatic “make-before-break” switchover is transparent to onboard VOBs

Communication Network Redundancy



Localization Error & Margin

600 m run —
worst-case 400 m
between beacons

Odometry drift
 $\pm 0.1\% \Rightarrow \pm 0.6\text{ m}$
($0.001 \times 600\text{ m}$)

Total clearance =
 $0.6\text{ m} + 8\text{ m} \approx 8.6\text{ m}$
($\approx 9\text{ m}$ envelope)


Fail-safe overlap
adds 8 m buffer



Power & Environmental Hardening

- 30-min runtime UPS in every wayside cabinet (ride-through brown-outs)
- Components qualified – 25 °C ... +55 °C to EN 50155 T3 / IEC 60571
- Enclosures sealed $\geq$ IP54 (EU) / NEMA 4 (NA); conformal-coated PCBs
- Fans & heaters with thermostat-controlled duty cycle < 30 % (energy)

Zone Controller Redundancy



Dual redundant
Zone-Controller pair
(hot-standby 2oo2)



Physically separate,
fire-rated racks



Automatic
switchover < 50 ms
on heartbeat loss



On-line self-test
every 2 s; MTTR
design target ≤ 4 h

Vital Onboard Controller Redundancy

Dual VOBCs run 2-out-of-2 vital voting

Separate tachometers, IMUs & A/B antennas


Failed channel auto-isolates—train keeps authority

Vital relay drop-out forces safe brake if disagreement >2 km/h

Graceful Degradation Mode

- ATO channel drops → driver takes over (ATP still vital)
- Radio link lost > 5 s → emergency brake, restrictive mode
- Zone-controller failure → adjacent ZC grants 25 km/h authority
- Manual fallback keeps $\leq 40\%$ service until fault cleared


ATO Fail



Network Segmentation & Zones

- - Enterprise IT zone strictly separated from railway OT
- - Grey DMZ buffers traffic & applies deep-packet inspection
- - Blue safety-critical signalling zone accepts *only* vital protocols
- - CCTV / ancillary systems isolated in gold zone
- - Firewalls implement IEC 62443 “conduit” least-privilege rules

Network Segmentation & Zones



Access Control & Authentication



Unique operator & maintainer accounts — MFA required for every remote log-in



Least-privilege, role-based permissions enforced on ATS / zone controller



Secure-boot chain + signed firmware prevent rogue code on vital CPUs

Monitoring & Incident Response

- OT-aware IDS (e.g., Cisco Cyber Vision) baselines CBTC traffic and flags anomalies in <10 s
- Central SIEM (Splunk / QRadar) correlates logs from ZC, ATS & firewalls for Tier-1 SOC triage
- Pre-built IR playbook: isolate radio AP VLAN, switch to backup channel, verify ATP heartbeat
- 24 × 7 SOC drills quarterly tabletops using real events (e.g., MTA 2021 & SFMTA 2022 ransomware)
- NIST 800-82 and IEC 62443-3-3 both stress *continuous* monitoring.

AI/ML in Predictive Maintenance



Rail IoT gateway streams axle-box vibration & CBTC radio KPIs to cloud every 60 s



Gradient-boost ML model flags anomaly score $> 0.85 \Rightarrow$ "AP-fail-in-7 days" ticket



Dashboard (Grafana-style) shows heat-map of AP MTBF & trend line of bearing RMS g



Pilot on 40 trains cut radio outages 40 % & saved ≈ 2 h mean-time-to-repair per event

AI/ML for Dynamic Scheduling



Cloud-based optimizer re-forecasts headway every 30 s using live APC counts & Bluetooth-probe demand heat-map



Algorithm elongates dwell ± 10 s at overloaded stations and simultaneously issues ± 7 km/h cruise tweaks to trailing trains



Pilot on Hong Kong MTR Tuen Ma Line (Dec-22 $\rightarrow$ Mar-23) cut worst-case platform crowding by 18 % and saved 5 % traction energy

5G & FRMCS for CBTC


- **Release-18 FRMCS** on 700 MHz/1900 MHz gives < 10 ms URLLC + 99.999 % availability for CBTC traffic
- **Coverage economics** – 5 G small-cells @ $\approx$ 250 m spacing (-95 dBm) vs Wi-Fi 6 APs @ 70 m; 5 G needs $\approx 3 \times$ fewer trackside sites
- **TCO snapshot (10 km guideway)** : Wi-Fi CAPEX $\approx$ US\$ 1.9 M + OPEX \$ 420 k/y; 5 G neutral-host lease $\approx$ \$ 2.4 M upfront but OPEX drops to \$ 240 k/y (-43 %)
- **Use-cases unlocked** : 4 K CCTV backhaul & edge AI, AR maintenance, broadband passenger Wi-Fi without a second network



Interoperability Initiatives

- **IEEE P1474.5 ‘Open CBTC Messages’** draft enables vendor-agnostic zone-to-train telegrams
- **UITP / ITxPT “Open CBTC Forum”** targets multi-vendor fleets before **2030** (first reference pilots in Copenhagen & Singapore)
- **EU-Shift2Rail X2Rail-1 / EULYNX** exports ETCS-style subsystem interfaces to metro CBTC to ease brownfield upgrades

Wrap-Up



Thank You.

- **Alexander Impastato**
- **Electrical and Computer Engineering M.S**
- **New York Institute of Technology**
- **L.K Comstock Railworks**
- 1-516-404-8830
- aimpastato888@gmail.com
- aimpasta@nyit.edu



Track Circuit vs CBTC Diagram

- Visual: Schematic comparing track circuit block detection
- CBTC beacon + radio for continuous detection
- Highlights legacy vs modern hardware footprint

Beacon & Odometry Example

- Visual: Train passes beacon every 300 m
- Odometry measures intermediate distance
- Error reset at each beacon read

Network Topology Example

- Visual: Dual ring fiber with access switches
- Redundant radio APs every 250 m
- Core routers at OCC

Case Study – London Underground

- Jubilee Line upgrade to CBTC (2011)
- Headway improved from 24 to 30 tph
- Project lessons: staff training & staged testing

Capacity Math Worked Example

- Given $v=60$ km/h, $a=1$ m/s², EB dist = 50 m
- Add 5 m error, 10 m overlap → 65 m gap
- Compare with 300 m fixed block gap

System Availability Metrics

- Target: >99.99% service uptime
- MTBF & MTTR for critical components
- Redundancy strategy meets KPI

Safety Integrity Level (SIL) Table

- SIL 1–4 probabilities of dangerous failure/hr
- CBTC vital functions => SIL 4
- Design & test rigor grows with SIL